

Digital Contact Pressure Gauges XY-PG825E

Typical Feature

- Dial diameter 80mm, with 4-Digits LED Display
- Relay output, Normally Open, Normally Closed
- Accuracy level: 0.5% FS
- Weld measurement pressure range(-100KPa~160MPa)
- Powered 12VDC; 220VAC and 380VAC are Optional
- Multi pressure multiunit switching (PSI/Kg.F/MPa)
- One key reset, alarm indication for peak and valley
- Set up alarm in whole measurement range



Brief Introduction

XY-PG825E is a Digital Contact Pressure Gauges, LED indicate Pressure, with same Electronic connection way with Mechanical Contact Pressure Gauge, which was built-in high accuracy pressure sensor, it displays real time pressure at short response time, the typical characteristics are high accuracy and excellent long-term stability, designed for Pressure Container, Air Compressor, Automated Machine, Hydraulic Machines and Plastic Injection Machines, it's very good alternative for Mechanical Contact Pressure Gauge.












The Contact Digital Pressure Gauges has 4-Digits LED display. There are 4 buttons on front panel to control Power On/Off and Setting. It is easy to install in pipeline, Isolation tank or others connects device, easy to set up operating parameter. Working condition is -20~80°C.

It has 304 stainless steel shell and connect joint, can be used in measuring gas, liquid, oil and other medium it is very good shock resistance and long working life.

XY-PG825E Contact Digital Pressure Gauges is powered by 24VDC; 220VAC and 380VAC are optional. Load capacity is 220VAC 5A; 380VAC 3A; 24VDC 2A; They have good Anti-Electromagnetic Interference, Surge Protection and Reverse Polarity Protection to against Harsh Working Condition.

There are weld measurement range -100KPa~160MPa, others measurement range are optional. Machinal joint include Thread, Flush Diaphragm, Clamp, Flange, Radiator and Differential Two-way Fitting.

Suggested Applications


-  Automatic Equipment
-  Mobile Working Machines
-  Medical Device
-  Pressure Container
-  Air Compressor
-  Automated Machine
-  Heat Pump Industry
-  Energy and Water Treatment System
-  Test Jig
-  Hydraulic and Pneumatic System
-  Customized Applications

More details for XY-PG825E, please contact us.


Specification

Model	XY-PG825E
Gauge Pressure Range	-0.1~0~0.2~1.0~1.6~5~10~25~40~60~100~160MPa
Mirco Pressure Range	0~5~10~25~40~60~100KPa
Pressure Type	Gauge Pressure Test; Vacuum Pressure Test
Dimension	Diameter Φ60;
Overload Capacity	200% (≤10MPa); 150% (>10MPa)
Measurement Medium	Gas or oil or other Liquid with Compatibility of SS 304 or 316
Accuracy Level	0.5%FS;
Long-Term Stability/Year	Typical: ±0.5% FS;
Sample Frequency	5 times/Second
Display	4 Digits LED
Operating temperature	-20~80°C
Compensation Temperature	-10~50°C
Power Supply	24VDC; 220VAC and 380VAC are optional
Alarm Indication	Relay signal (Normally Open, Normally Closed)
Load Capacity	220VAC 5A; 380VAC 3A; 24VDC 2A
Electronic Connection	5 Pins Connivers


Dimension(mm)



Mechanical Connection(mm)



OUTLET LINE:



Function	Connecting Method
Replacement of digital electric contact pressure gauge	Low pressure alarm: brown High pressure alarm: yellow Common port: green+blue
Low pressure to contact high pressure to break	Output: brown+green Setting AL and hysteresis Ad1
Low pressure to break high pressure to contact	Output: yellow+blue Setting AH and hysteresis Ad2
Two groups high pressure alarm (high pressure to contact)	1 group: white+green (settingAL) 2 group: blue+yellow (settingAH)

Eg: When pressure increases to 10 bar, the relay breaks; and decreases to 4 bar, the relay contacts. Use the 1 group relay to control, setting AL 4 bar and Ad1 6 bar. Use the 2 relay group to control, setting AH 10 bar and Ad2 6 bar.

How To Order

XY	PG	280	E	P	60M	I	P2	J	M3	B1	T1	L														
Category	Type	Setup	Pressure Connection	Pressure Range	Accuracy	Power	Output	Thread	Electrical Connection	Medium Temperature	Additional															
PG	Pressure Gauge	280	High Accuracy	E	Lower Mount	None	General Thread	XK	(0-30Pa)	1	0.40%	P0	Battery	R	RS485	M1	M20*1.5	B	Cable Outlet	T1	-5~40°C	LC	LED Display			
		210	High Accuracy Pressure&Temperature	Z	Panel Mount	P	Diaphragm Seals	>B	(0~8Bar)	2	0.20%	P2	24V	A	±20mA	M2	G1/4	C	Circular Connector	T2	-20~80°C	LE	LED Display			
		270	Explosion-Proof	G	Wireless	DP	Differential Pressure	>M1	(0~30Pa)	3	0.10%	PA	220V	J1	Relay	M3	G1/2	CC	Customized	T3	Customized	T	Explosion-Proof			
		280	80mm Dial Size LCD Display	F	Peak-Record	KF	Clamp	CC	Customized	4	0.50%	PS	380V	J2	Dual Relay	M4	1/2NPT									
		280	60mm Dial Size	V	Vacuum Switch	DN	Flange			5	0.25%	P6	12V	CC	Customized	M5	1/4NPT									
		380	100mm Dial Size	W	Water Pump Switch	9999	Customized			9	Customized	PS	Customized			M7	G1/4									
		380	80mm Dial Size LED Display													M9	Customized									
		560	Digital Remote Transmission																							
		625	Contact 60mm Dial Size																							
		825	Contact 80mm Dial Size																							
925	Contact 90mm Dial Size																									
PS	Pressure Switch	638	60mm Dial Size																							
		838	80mm Dial Size																							
		938	100mm Dial Size																							
		650	Switch Box with Plastic Shell																							
680	Switch Box with Full Metal Shell																									
780	Mechanical																									
PC	Pressure Control	680	60mm Dial Size																							
		880	80mm Dial Size																							
		980	100mm Dial Size																							

Remark: 1. This form is for whole Pressure Measurement and Pressure Control products, please read Product Date Sheet to get reference informations
2. If you may not find right information in this form, Please contact us to get future details

Shanghai XuYan Precision Technology Co., Ltd.

Address: No. 969, YunHan Road Pudong District Shanghai City China

Tel: +86 21 59241315

Email: sales@xvyanprecision.com

Website: www.xvyanprecision.com

Product Manager: Tyler Tou

Cell: +86 189 1797 0680

Email: ttao@Xuyanpercision.com